



***Stat Fax*® 4500**

Chemistry Analyzer

The Stat Fax® 4500 is a compact, standalone chemistry analyzer. Its streamlined design offers touch screen interface, superb optics, on-board curve-fitting software, and built-in printer to meet the requirements of modern laboratories.



AWARENESS TECHNOLOGY, Inc. PO Drawer 1679, Palm City, FL 34991 (772) 283 6540 fax (772) 283 8020
web site: <http://www.awaretech.com>, email: info@awaretech.com

Cost Effective by Design®

Stat Fax[®] 4500

Chemistry Analyzer Specifications

Photometric

Linear Measurement Range:
Photometric Accuracy:
Stability:
Light Source:
Standard Wavelengths:

Filter Type:
Tube Size:
Minimum sample volume:

Tube or Cuvette - 0.0 to 3.0 Absorbance units (A).
+/- (1% of the reading + 0.005A).
Drift of no more than 0.005A in 8 hours/bichromatic.
Tungsten lamp with lamp saver feature.
340, 405, 505, 545, 580 and 630nm.
(alternate filters available from 340 to 700nm).
IAD hardcoat interference, 10nm half bandpass.
12 mm round is standard.
1mL for 12mm round tube.

Electronic

Display:
Printer:
Power Requirements:
Microprocessor:
Interface:

Interactive touch-screen 3.5" LCD, color graphic display.
Thermal dot matrix, with graphic capability.
115V or 230V AC, 1.5A, 50-60Hz (universal input).
eZ80
USB mouse.

Software

Speed:
Calculation Modes:

Test Menu:

Reads, calculates and prints results, 3 seconds per tube.
Single point calibration by standard or factor, multipoint calibration with point-to-point curve fit, rate by standard or factor (batch or singly).
More than 50 open channels to store tests.
Stores all parameters including wavelengths, calculations, unit codes, linear and normal ranges, rate timing, standard values, test names and previous standard curve.

Other

Temperature control
Enclosure:
Dimensions:
Certifications:

Read cell and incubation block, user selectable.
Painted flame-retardant ABS plastic cover and base.
Approx. 9x13.5x5in. (24x34x13cm) weighs 10lbs.(4.5kg).
NRTL listed, CE mark.

